



OUTDOOR LIGHTING SOLUTION

LOONLUX SL



PRODUCT INFORMATION

IP65 LED luminaire with adjustable bracket for installation and power ranging from 50 W to 200 W. With a lifetime of 50,000 (L70) hours and efficiency going up to 130 lm/W, these light fixtures are perfect to meet any outdoor place, warehouse, tunnel, or venue site, lighting requirement.

APPLICATION

- Outdoor lighting places
- Parking lot
- Stadiums and other outdoor venue sites
- Urban street highway-rail transit
- Tunnel and other underground passage
- Workshop
- Large warehouse
- Industrial areas
- Billboards

FEATURES & BENEFITS

- Efficacy up to 130 lm/W
- Easy mounting; adjustable 180° bracket for installation
- IP65 protection class
- 5-year warranty

LOONLUX SL

5 YEARS WARRANTY

IP65

RoHS Compliant

CE

WEEE


F

GENERAL INFORMATION


SUPPLY VOLTAGE	198 – 264 V; 50/60 Hz
POWER FACTOR	>0.95
LED CHIP	3030
EFFICACY	130Lm/W ± 3%
CCT	4000 K ± 150 K (natural white)
CRI	>80
OPTICS	90° 130x80°
IP CLASS	IP65
IK CLASS	IK07
CERTIFICATION	CE, ROHS
OPERATING TEMP.	-25°C ~ +50 °C
LIFETIME	L70 50 000 h (Ta +25°C)
INSTALLATION OPTIONS	wall mount
WARRANTY	5 years



LIGHT DISTRIBUTION GRAPH



— C0-180 - - - C90-270 90°



— C0-180 - - - C90-270 30°x80°

ORDERING INFORMATION

SKU	OPTICS	POWER, W	LUMEN OUTPUT, LM	DIMENSIONS, MM	STATUS
BFLP-SL-A30x80840E50	30°x 80°	50	6500	287×211×47	PRE-ORDER*
BFLP-SL-A90840E50	90°	50	6500	287×211×47	PRE-ORDER*
BFLP-S-LA30x80840E100	30°x 80°	100	13000	361×259×51	IN STOCK
BFLP-SL-A90840E100	90°	100	13000	361×259×51	PRE-ORDER*
BFLP-SL-A30x80840E150	30°x 80°	150	19500	450×335×52	PRE-ORDER*
BFLP-SL-A90840E150	90°	150	19500	450×335×52	PRE-ORDER*
BFLP-SL-A30x80840E200	30°x 80°	200	26000	476×361×61	PRE-ORDER*
BFLP-SL-A90840E200	90°	200	26000	476×361×61	PRE-ORDER*

*Pre-order products will be available only with MOQ from 100pcs, lead time ~8 weeks. For precise lead time, contact your Customer Service manager.