



HERONLUX SM

PRODUCT DESCRIPTION

HeronLux SM - surface mounted downlight luminaire, an ideal solution for your office lighting. Due to its versatility, HeronLux luminaires are also perfect to illuminate such spaces as corridors, shopping centers, hallways and etc.

APPLICATION

- Offices
- Hallways
- Shopping centres
- Technical rooms
- Common rooms
- Showrooms

FEATURES & BENEFITS

- Available options from 1294 lm up to 1888 lm
- IP20 protection class
- 5 year warranty
- Easy installation


HERONLUX SM

GENERAL INFORMATION

SUPPLY VOLTAGE	220 - 240 V, 50-60 Hz
POWER FACTOR	0.90
EFFICACY	108 – 126 lm/W
CCT	4000 K ± 150 K (natural white)
CRI	>80
BEAM ANGLE	90°
IP CLASS	IP20
RECOMMENDED HEIGHT	from 2 to 6 meters
OPERATING TEMP.	-15 °C ~ +40 °C
STORAGE TEMP.	+5 °C ~ +50 °C
LIFETIME	L80B10 50 000 h (Ta +25 °C)
MOUNTING OPTIONS	surface mounted
CERTIFICATION	CE compliant
WARRANTY	5 years



LIGHT DISTRIBUTION GRAPH



— C0-180 — C90-270 90°

ORDERING INFORMATION

SKU	POWER, W	LUMEN OUTPUT, LM	DIMENSIONS, MM	WEIGHT, KG
BDNP-SM-D150A90840I12	12 ± 3%	1294 ± 3%	Face/height: Ø150*120	1.10
BDNP-SM-D190A90840I15	15 ± 3%	1888 ± 3%	Face/height: Ø190*120	1.51